


6-Dec-16
13:45:59

1
1 ms
1.00 V

2
1 ms
1.00 V

3
1 ms
1.00 V

4
1 ms
1.00 V



2754 sweeps: average low high sigma
rms(1) 2.291 V 1.819 2.389 0.097
rms(2) 184mV 151 212 14
rms(3) 2.253 V 1.800 2.348 0.092
rms(4) 716mV 437 771 58
phase(1,3) -89 ° -96 -85 2


1 1 V AC
2 1 V AC
3 1 V AC
4 1 V AC





Ext10 DC 0.05 V 1MΩ

10 MS/s


NORMAL









6-Dec-16
14:22:46





Startup

Printer Name:	ColorQube 8570DN-25
Page Count:	4456
Serial Number:	XFN180554
Activation Date:	SAT JUN 21 03:40:45 2014
Adobe® PostScript® 3™:	3016.101 (16)
PCL 5c Version:	5.0
Firmware Versions:	System 1.3.8.P / OS 10.62 / PS 4.10.0 / Eng 23.P1.4.10.0 / Net 42. 40.09.02.2011
Firmware Updated:	Factory Original
PLDs:	FPGA 1954_7.21 / PC 13 / IO 4 / IL 16 / PS HW2.30 SW1.00 / HEAD 3 / HCF1 NA / HCF2 NA / HCF3 NA
Installed RAM:	512 MB
ROM Fonts Available:	137 PostScript®, 81 PCL®
Hard Disk:	Not Connected
Duplex Unit:	Installed
Print Quality:	Enhanced
Color Correction:	Automatic
USB 2.0:	Language: AutoSelect
Ethernet®:	PhaserShare® Series B Interface for Ethernet® Network 1000Base-T full duplex, 9C:93:4E:34:6A:8E
802.1X:	Disabled
EtherTalk®:	LaserWriter@*, Node ID: 65502.221
TCP/IP:	Confirmed DNS Name: None IPv4 Address: 192.168.30.100 IPv6 Disabled
Web Page:	http://192.168.30.100





The Startup page prints each time you power up the printer. To turn off this page:

1. At the printer's control panel, select "Printer Setup" then press "OK".
2. Scroll to "Printer Controls" and press "OK".
3. Toggle the "Startup Page" setting to "Off".




Adobe, PostScript, and PostScript 3 are trademarks of Adobe Systems Incorporated which may be registered in certain jurisdictions. PANTONE® and PANTONE CALIBRATED™ are trademarks of Pantone, Inc.
Printed On: Dec 7, 2016, 2:36:28






6-Dec-16
14:36:53



Analog Scan

Dec 06, 2016 02:40:38 PM


Torr



Analog Scan

Torr


Dec 06, 2016 02:41:23 PM



Analog Scan

Dec 06, 2016 02:47:54 PM


Torr



Analog Scan

Torr


Dec 06, 2016 02:52:35 PM





Torr

Analog Scan

Dec 06, 2016 02:52:35 PM
X = 65.0 Y = 0.00e+000







6-Dec-16


15:04:55

1
1 ms
1.00 V

2
1 ms
1.00 V

3
1 ms
1.00 V

4
1 ms
1.00 V



1803 sweeps: average low high sigma
rms(1) 2.193 V 1.946 2.376 0.099
rms(2) 218mV 178 246 17
rms(3) 2.135 V 1.905 2.279 0.088
rms(4) 610mV 496 675 31
phase(1,3) -88 ° -94 -85 2

1 1 V AC
2 1 V AC
3 1 V AC
4 1 V AC



Ext10 DC 0.05 V 1MΩ

10 MS/s

NORMAL


6-Dec-16
15:42:21

1
1 ms
1.00 V

2
1 ms
1.00 V

3
1 ms
1.00 V

4
1 ms
1.00 V



225 sweeps: average low high sigma

rms(1) 2.369 V 2.190 2.462 0.046

rms(2) 232mV 216 244 7

rms(3) 2.291 V 2.118 2.373 0.041

rms(4) 681mV 585 703 13

phase(1,3) -88 ° -93 -85 2

1 ms

1 V AC

1 V AC

1 V AC


1 V AC



Ext10 DC 0.05 V 1MΩ

10 MS/s

NORMAL



Analog Scan

Torr

X = 1.0 Y = 7.84e-011

